



PART NUMBER		SPECIFICATIONS						
TCL-36-12-F	TCL-36-12-SS	2-1/4-12	3-1/4	1.375	3.504	0.750	5/16-24	
BLACK OXIDE STEEL	STAINLESS STEEL	BORE B	OUTER DIAM. OD (mm)	SCREW LOCATION R (mm)	CLEARANCE DIAM. C (mm) MAX	WIDTH W (mm)	FORGED CLAMP SCREW	
MTCL-4-0.7-F	MTCL-4-0.7-SS	M4x0.7	16	5.5	20.8	9	M3	
MTCL-5-0.8-F	MTCL-5-0.8-SS	M5x0.8	16	5.5	20.8	9	M3	
MTCL-6-1-F	MTCL-6-1-SS	M6x1	16	5.5	20.8	9	M3	
MTCL-8-1.25-F	MTCL-8-1.25-SS	M8x1.25	18	6.5	22.4	9	M3	
MTCL-10-1.5-F	MTCL-10-1.5-SS	M10x1.5	24	8.5	26.3	9	M3	
MTCL-12-1.75-F	MTCL-12-1.75-SS	M12x1.75	28	10.0	32.0	11	M4	
MTCL-16-2-F	MTCL-16-2-SS	M16x2	34	12.5	39.3	13	M5	
MTCL-20-2.5-F	MTCL-20-2.5-SS	M20x2.5	40	14.7	47.4	15	M6	
MTCL-24-3-F	MTCL-24-3-SS	M24x3	45	29.5	52.1	15	M6	
MTCL-30-3.5-F	MTCL-30-3.5-SS	M30x3.5	54	21.5	59.2	15	M6	

**Note:** Sizes TCL-28 through TCL-36 do not have backslot.

- Does not mar the shaft.
- Single point faced.
- Acme and Left-hand threads available.
- Additional sizes available.
- Width tolerance: +.003"  
-.010"